

7260BT-7270BT

Axion MSR™ Eye/Face Wash



FEATURES & BENEFITS

Strainers/Filters

Chrome-plated brass in-line 50 x 50 mesh water strainer prevents debris from reaching the eyewash so the unit stays functioning at its best. Strainer is easily serviceable.

Trap

1-1/4" chrome-plated brass trap with tailpiece allow for the emergency equipment to meet desired requirements for wall mounting.

Quality Control

Eye/face wash and valve assembly is pre-built and fully water/pressure tested to ensure no leaks and proper function which ultimately reduces installation time and gives the end contractor an added peace of mind. Unit also ships with pre-assembled cast-aluminum wall bracket to assist in the installation process.

Eye/Face Wash

AXION MSR™ eye/face wash head uses an inverted directional laminar flow to sweep contaminants away from the vulnerable nasal cavity.

Antimicrobially Treated

AXION MSR™ eye/face head is antimicrobially treated using the natural protection of silver. Impregnating these components with silver helps protect the head against the growth of mold and mildew on the treated components. AXION MSR™ is the only eye/face product on the market to feature antimicrobial protection.

Bowl

The 11" round green ABS plastic receptor is resistant to damage from alkalis, salt solutions, oils and most acids.



SPECIFICATIONS

Model 7260BT-7270BT wall mounted eye/face wash shall include a green ABS plastic 11" bowl, an antimicrobially treated AXION MSR™ eye/face wash head to help protect against the growth of mold and mildew on the treated components, and shall feature inverted directional laminar flow which achieves zero vertical velocity supplied by an integral 3.7 gpm flow control, chrome-plated brass stay-open ball valve equipped with stainless steel ball and stem, tail piece and trap, and chrome-plated brass in-line 50 x 50 mesh water strainer. Unit shall also include cast-aluminum chromate protected wall bracket, yellow plastic pop-off dust cover for eyewash head, universal sign, 1/2" IPS inlet, and 1-1/2" IPS waste.

OPTIONS

- Repair Kit: Model VRKEWSTR is a repair kit for SP507 and SP509. Includes screen and gasket.
- Tempered Water Blending Systems: Model TWBS.EW is a prepackaged, fully engineered and tested system with fail-safe features to produce up to 5 gpm tempered water for eye/face washes (Pat.# 5,350,112).
- Tempered Water Blending Systems: Model TWBS.EW.H is a prepackaged instantaneous electrical water heater, 480 VAC/3 phase/18 KW, fully engineered and tested system with fail-safe features to produce up to 2.5 gpm tempered water for eye/face washes.
- Tempered Water Blending Valves: Model 9201, is a thermostatic mixing valve that mixes hot and cold water for the tempering of eye/face wash units at a maximum flow rate of 20 gpm.

To see all options for this model, visit www.hawasco.com.

APPLICATIONS

Where the eyes of any person may be exposed to injurious or corrosive materials, suitable facilities for quick flushing and cleansing of the eyes must be provided within the work area for immediate emergency use. Emergency eyewash facilities shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 7260BT-7270BT is certified by CSA to meet the ANSI Z358.1-2004 Standard for Emergency Eyewash and Shower Equipment.

